

Pneumatic hoses

Blue PUR Ultraflex 2



Pneumatic hoses Blue PUR Ultraflex 2

Ultra flexible recoil hoses, capable of bending without being damaged. Maintains persistent flexibility at temperatures as low as -40°C. An oil-resistant hose whose superior qualities are acknowledged in all sectors of industry. We recommend that polyurethane hoses not be used in direct sunlight for long periods of time.

Technical data

Material: Polyurethane (100% PUR)
 Working pressure: Max. 20 bar at +23°C
 Burst pressure: 60 bar at +23°C
 Temp. range: -40°C to +70°C
 Surface hardness: Shore A 80 ± 2

Pneumatic hoses Blue PUR Ultraflex 2 with JWL coupling & Euro nipple

Connection	Dim.	Work. length	Max. work. pressure	Code no.
Series 510 coupling & nipple	ø8 x ø12mm	10m	20 Bar	1791002-10510
Series 510 coupling & nipple	ø8 x ø12mm	20m	20 Bar	1791002-20510
Series 510 coupling & nipple	ø10 x ø14mm	10m	20 Bar	1791004-10510
Series 510 coupling & nipple	ø10 x ø14mm	20m	20 Bar	1791004-20510
Series 520 coupling & nipple	ø8 x ø12mm	10m	20 Bar	1791002-10520
Series 520 coupling & nipple	ø8 x ø12mm	20m	20 Bar	1791002-20520
Series 520 coupling & nipple	ø10 x ø14mm	10m	20 Bar	1791004-10520
Series 520 coupling & nipple	ø10 x ø14mm	20m	20 Bar	1791004-20520
Series 520 coupling & nipple	ø8 x ø12mm	10m	20 Bar	1791002-10530
Series 520 coupling & nipple	ø8 x ø12mm	20m	20 Bar	1791002-20530
Series 520 coupling & nipple	ø10 x ø14mm	10m	20 Bar	1791004-10530
Series 520 coupling & nipple	ø10 x ø14mm	20m	20 Bar	1791004-20530

Pneumatic hoses Blue PUR Ultraflex 2 with 1/4" external thread

Connection	Dim.	Work. length	Max. work. pressure	Code no.
1/4" external thread	ø8 x ø12mm	10m	20 Bar	179000200-1012
1/4" external thread	ø8 x ø12mm	20m	20 Bar	179000200-2012
1/4" external thread	ø10 x ø14mm	10m	20 Bar	179000300-1012
1/4" external thread	ø10 x ø14mm	20m	20 Bar	179000300-2012



17910002-10520



179000200-1012